

Q-SYS NVM-302D

Network video decoder

KEY FEATURES

- Q-SYS native video decoder
- Mediacast AV routing paradigm enables high-quality, network-efficient video distribution at scale
- Supports resolutions up to 4K60 4:4:4
- RS-232 and IR connectivity for third-party device control
- AV Bridging via USB-C (supported in a future firmware update)



The Q-SYS NVM-302D is a network HDMI decoder that comes pre-installed with a single-channel decode video app. Q-SYS NVM Series network video endpoints deliver high-quality, low-bandwidth network video at scale to a broad range of spaces for hospitality, entertainment, collaboration, government and more.

SCALE Q-SYS VIDEO EXPERIENCES

The NVM Series NVM-302D decoder comes pre-installed with a single-channel decode video app.

Q-SYS NVM Series video endpoints expand the existing video use cases for your Q-SYS systems, pairing low-density HDMI I/O with network-efficient AV transport to deliver Q-SYS network video that is purpose-built for large-scale deployments into a broader range of spaces from entertainment and hospitality to collaboration, government and more.

NVM Series are designed on a software paradigm that reduces the reliance on single-purpose hardware and is ready for future feature updates and additional video apps that will allow your Q-SYS system to evolve alongside your business needs.

DESIGN NATIVELY. DEPLOY FASTER.

The new NVM Designer tool is an intuitive method for configuring and deploying large scale video systems natively within Q-SYS Designer Software, the singular software program that enables the rest of your system design, including DSP programming, AV routing and user control interface design. NVM Designer enables no-code deployment of hundreds of endpoints in minutes, without the need for additional video matrix or management hardware.

DELIVER HOLISTIC Q-SYS EXPERIENCES.


Driven by the Q-SYS Full Stack AV Platform, NVM Series video endpoints leverage an integrated audio, video and control engine that streamlines system integration, from no-code workflows and end-to-end automation to comprehensive user control, making it even easier to expand the Q-SYS experience into more types of application spaces.

The NVM Series **NVM-302D** decoder includes a pre-installed, single-decode streaming video app (NVM-D1).

SUPPORTED VIDEO FORMATS

Resolution		Frame rate (Hz)	Chroma sampling level	Bit Depth
4K (UHD/DCI)	3840×2160, 4096×2160	23.976/24, 25, 29.97/30, 50, 59.94/60	4:4:4	8 bit
FHD/FHD+	1920×1080 (1080p), 1920×1200	23.976/24, 25, 29.97/30, 50, 59.94/60	4:4:4	8 bit
HD	1280×720 (720p)	23.976/24, 25, 29.97/30, 50, 59.94/60	4:4:4	8 bit
Ultrawide (21:9)	3440×1440, 2560×1080	23.976/24, 25, 29.97/30, 50, 59.94/60	4:4:4	8 bit
PC Resolutions	2560×1440, 2560×1600	60	4:4:4	8 bit
SD (NTSC)	720×480	29.97/30, 59.94/60	4:4:4	8 bit
SD (PAL)	720×576	25, 50	4:4:4	8 bit
VGA	640 × 480	59.94/60	4:4:4	8 bit

- 4:2:2 & 4:2:0 Chroma subsampling supported at some resolutions.
- The scaler is capable of operating in three modes (configurable within Q-SYS Designer Software):
 1. Stretch-to-fit
 2. Maintain aspect ratio
 3. 1:1 pixel mapping



VIDEO I/O

HDMI 2.0 output	1x HDMI 2.0 output capable of transmitting output video formats up to 4K60 4:4:4 when using NVM-D1 application HDCP 2.3 and 1.4 supported
-----------------	--

AUDIO I/O

HDMI inputs	8-channel PCM audio, Q-SYS routable
-------------	-------------------------------------

GENERAL

Dimensions	7.3 × 5.2 × 1.2 in (185 × 131.5 × 30.5 mm)
Weight	1.75 lbs (794 g)
Mounting options	Surface mounting hardware included; compatible with NV-RK accessory for rack mounting

OTHER

RS-232	1x RS-232 (3.5mm pitch euro-block)
IR transmit	1x IR Transmit (3.5mm mini jack)
USB-C	USB 3.2 Gen 1 Type-C Device Port - Device Mode and Host Mode supported - Video bridging supported in future firmware release - HID routing supported - 5V, 900 mA (total, shared across all USB peripherals)
USB-A	2x USB 3.2 Gen 1 - 5V, 900 mA (total, shared across all USB peripherals) - HID routing supported
LAN	2.5GBASE-T compliant
Power over Ethernet	PoE+, 802.3at Type 2, Class 4 (25.5 W at PD, 30 W at PSE)

ENVIRONMENTAL

Ambient operating temperature range	32° to 104° F (0° - 40° C)
Humidity	5 to 90 RH % non-condensing
Storage temperature	-4° to 158° F (-20° to +70° C)
What's in the box?	NVM-302D video endpoint Euro-terminal connectors for RS-232 Surface mounting accessories Safety and warranty statements

PERIPHERAL LIMITS

Audio channels	Each routing group consumes 1x audio channel; The NVM-302D consumes 1x audio channel when breakout audio is enabled. Limitations of audio channels is based on the Q-SYS Core used in the design.
Video limitation	Limitations of video endpoints is based on the peripheral limits of the Q-SYS Core used in the design.